

SoundPro 40

PRODUCT OVERVIEW

Australian Architectural Fire Doors have developed the tested & approved 'SoundPro' acoustic door range. Specifically designed & engineered to minimize or block the transmission of sound & vibration between spaces. SoundPro Door Systems are:

- Manufactured locally in QLD under ISO 9001 Quality Standards
- Tested to Australian Standards ISO 354-2006 & AS 2107-2000
- Available in a variety of RW (weighted sound reduction) ratings

DETAILS

Product	RW	Fire rating	Weight	Maximum Size	Door thickness	Perimeter Seal	Meeting stile Seal	Drop Seal	Threshold Plate	Frame	Test Ref #
SoundPro 40 - Single	RW40	N/A	27.3kg/m2	2100 x 920	73mm	IS1515 Flexi-Wing IS7087si	N/A	IS8520si	Flat	2mm steel frame, plaster filled	AC-PR134A-JPJ-01 Test AC399DR PKA100AFD R02
SoundPro 40 - Double	RW40	N/A	27.3kg/m2	2100 x 920 2100 x 920	73mm	IS1515 Flexi-Wing IS7087si	IS7061 (2-Off)	IS8520si	Flat	2mm steel frame, plaster filled	PKA100AFD R02

SIZES:

Single: 2100 x 920 x 73

Pair: 2100 x 920/920 x 73

Further sizes available upon request. Please contact your AAFD representative.

SEALS:

Acoustic door sets are supplied standard with tested & approved seal combinations

FRAME:

Pressed metal frame

2mm Mild Steel & Stainless Steel

Up to **400mm** material girth

Frame fixings

100 x 75 x 3mm ball bearing hinges

FINISH OPTIONS:


Manufacture, supply, installation, Inspection, certification & maintenance of the following products:

- Ply or MDF
- Laminate – Antibacterial
- STD
- HPL
- Veneer
- Metal (mild steel, aluminium, colour bond)


'SoundPro 40'

DOOR SEAL COBINATION:


Perimeter seal: IS1515



Perimeter seal: IS7087si



Threshold automatic drop seal: IS8520si



Dual leaf door meeting stile: IS7061si x 2

